

APPLICATIONS

This kit is designed to convert most recessed fluorescent 2x2 and 2x4 troffers and parabolics to long-life and efficient LED technology. These kits provide everything required to enhance the performance and energy savings of your recessed fixture while minimizing labor, clean up and expense. Kits include high- efficiency reflector with PowerCor, LED boards and tek screws for easy assembly. Kits install with simple hand tools in minutes.

FEATURES & BENEFITS

- ♦ BriteCor AC Direct technology - No DC power supply
- ♦ Input Voltage: 120, 277V
- ♦ Optional 0-10V dimming
- ♦ Reflectors are precision formed and high performance
- ♦ ETL Listed for dry locations

SPECIFICATIONS

The BTRK retrofit kits mount easily, requiring only simple hand tools. The process includes removal of the existing ballast cover(s) and removal of the existing socket brackets and ballast. The 42:CW91I2920/6820C is 80 the backside of the reflector.

ORDERING DATA

EXAMPLE: BTRK-22-20-2-4080/SC

BTRK						
Series	Size	Wattage		Driver Voltage	Color Temp/CRI	Options
BTRK	22 2x2 24 2x4	<u>Standard 2x2</u> 20 20 Watts	<u>Standard 2x4</u> 0 30 Watts 40 40 Watts	1 120V 2 277V 1D 120V - low THD 2D 277V - low THD	<u>First 2 Digits Temp</u> 30 3000K 35 3500K 40 4000K 50 5000K 57 5700K <u>Second 2 Digits CRI</u> 80 80 CRI Standard 90 90 CRI	<u>Dimmer (Blank)</u> SC SmartCor



Dimensions and specifications subject to change without notice.

Project Name:

Catalog Number:

Fixture Type: